

Cable for 4000 Visual Nurse Call Systems CB-4002



CB-4002



Description: Cornell's SmartWire™ Cable is one of the select cables available for wiring the Cornell 4000 Visual Nurse Call System.

Agencies Approvals

NEC Article 800, 760; UL Listed C(UL)US CMR OR FPLR (UL), RoHS Compliant

Technical Information:

Description: 22 AWG 2 Conductor Bare Copper, Non-Shielded Non-Plenum, UL Listed C (UL) US CMR OR FPLR (UL)

Conductor Description: 22 AWG (7/30 Bare Copper)

Insulation: PVC .008

Color Code: Black/White

Shield: N/A

Drain Wire: N/A

Jacket: PVC .018"

Jacket Color: Gray Jacket with Blue Stripe

Marking: SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMR OR FPLR (UL) 75C ROHS MADE IN THE USA

Overall Diameter: .126" Nom.

Cable Weight: 9 Lbs/Mft.

Capacitance: 20 pF/Ft. Nom.

Impedance: 94 Ohms/Mft.

Temperature and Voltage Rating: 0C to 75C/ 300 Volt

Length: 1,000 ft. +/-5%

Made in the USA, 425102

Cable, Plenum for 4000 Visual Nurse Call Systems CB-4002P



CB-4002P



Description: Cornell's SmartWire™ Cable is one of the select cables available for wiring the Cornell 4000 Visual Nurse Call System.

Agencies Approvals

NEC Article 800, 760; UL Listed C(UL)US CMP OR FPLP (UL), RoHS Compliant

Flame Rating: Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

Technical Information:

Description: 22 AWG 2 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C (UL) US CMP OR FPLP (UL)

Conductor Description: 22 AWG (7/30 Bare Copper)

Insulation: Low-Smoke PVC .008

Color Code: Black/White

Shield: N/A

Drain Wire: N/A

Jacket: Low-Smoke PVC .018"

Jacket Color: White Jacket

Marking: SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP OR FPLP (UL) ROHS MADE IN THE USA

Overall Diameter: .126" Nom.

Cable Weight: 9 Lbs/Mft.

Capacitance: 20 pF/Ft. Nom.

Impedance: 94 Ohms/Mft.

Temperature and Voltage Rating: 0C to 75C/ 300 Volt

Length: 1,000 ft. +/-5%

Made in the USA, 444360

