

## Cable for 4000 Visual Nurse Call Systems CB-4004



CB-4004



**Description:** Cornell's SmartWire™ Cable is one of the select cables available for wiring the Cornell 4000 Visual Nurse Call System.

Agencies Approvals

NEC Article 800, 760; UL Listed C(UL)US CMR OR FPLR (UL), RoHS Compliant

### Technical Information:

Description: 18 AWG 4 Conductor Bare Copper, Non-Shielded Non-Plenum, UL Listed C (UL) US CMR OR FPLR (UL)

Conductor Description: 18 AWG (7/26 Bare Copper)

Insulation: PVC .008

Color Code: Black/Red/White/Green

Shield: N/A

Drain Wire: N/A

Jacket: PVC .018"

Jacket Color: Gray Jacket

Marking: SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMR OR FPLR (UL) 75C ROHS MADE IN THE USA

Overall Diameter: .184" Nom.

Cable Weight: 33 Lbs/Mft.

Capacitance: 26 pF/Ft. Nom.

Impedance: 70 Ohms/Mft.

Temperature and Voltage Rating: 0C to 75C/ 300 Volt


Length: 1,000 ft. +/-5%

Made in the USA, 427300

## Cable, Plenum for 4000 Visual Nurse Call Systems CB-4004P



CB-4004P



**Description:** Cornell's SmartWire™ Cable is one of the select cables available for wiring the Cornell 4000 Visual Nurse Call System.

### Agencies Approvals

NEC Article 800, 760; UL Listed C(UL)US CMP OR FPLP (UL), RoHS Compliant

Flame Rating: Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

### Technical Information:

Description: 18 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C (UL) US CMP OR FPLP (UL)

Conductor Description: 18 AWG (7/26 Bare Copper)

Insulation: Low-Smoke PVC .008

Color Code: Black/Red/White/Green

Shield: N/A

Drain Wire: N/A

Jacket: Low-Smoke PVC .018"

Jacket Color: White Jacket

Marking: SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP OR FPLP (UL) 75C ROHS MADE IN THE USA

Overall Diameter: .184" Nom.

Cable Weight: 32 Lbs/Mft.

Capacitance: 26 pF/Ft. Nom.

Impedance: 72 Ohms/Mft.

Temperature and Voltage Rating: 0C to 75C/ 300 Volt

Length: 1,000 ft. +/-5%

Made in the USA, 442380

