


Alphanumeric Pager PP-9000AW-2



Description: The PP-9000AW-2 Alphanumeric Pager is a true mini pager with large display and user friendly interface. It can be either selective PC or hand programmable. The pager device also has 16 memory slots, 10 personal slots, a full message indicator, and supports multiple languages (English, Spanish, Portuguese, Russian, German, and French). Includes:

- 84 Alphanumeric or Chinese character
- Back lit display
- Long battery life, with Lithium battery back-up
- 4 beep alerts, 10 melody alerts, vibrate mode, 9

caller ID activated beep tones, reminder alert, and 5 daily alarm sets

Duplicate message detection, unread message display, message time stamp, month/date/year/time display

- Extension compatible
- Up to 6 cap code capability
- Selective message lock/delete Frequency: 138\74MHz, 279\282MHz, 443\473MHz, 929\932\MHz
- Paging Sensitivity: 512bps 5u V\M, 1200bps 9u V\M
- Bit Rate: 512\1200\2400bps for POCSAG, 1600\3200\6400bps for FLEX
- Spurious Rejection: 40db below carrier
- Alert Tone Volume: 85db at 30cm (12")
- View Area: 45 x 14.43mm

Operation: When used with Cornell System, this pager keeps you connected and available 24/7.

Engineering Specifications: Contractor shall furnish, program and include Pocket Pagers Model PP-9000AW-2 according to specifications

Technical Information:

Dimensions: 64 x 43 x 20mm

Power: 3.0V Lithium

Battery Replacement: Duracell DL123A lithium battery

Battery Life: Up to 2 years

Operating Environment: 50-120°F Indoor Non-condensing

